



گروه فنی مهندسی جوش و برش مقدم

اعتماد از شما کیفیت و تخصص از ما



09153223758



051-37581400



<https://www.moghadamwelding>



<http://instagram.com/moghadam>



<https://t.me/moghadamwelding>



<https://whatsapp.com/channel>



<https://rubika.ir/moghadamwelding>



مشهد خیام شمالی 63 خیابان پردیس 3

برای کسب اطلاعات بیشتر بر روی لینک ها کلیک کنید

- 7 سال سابقه آموزش تعمیرات تخصصی دستگاه های جوش اینورتری تک فاز و 3 فاز
- 7 سال سابقه فروش قطعات الکترونیکی دستگاه جوش تک فاز و 3 فاز
- آموزش تخصصی تحلیل دستگاه های جوش اینورتری مختص ابراز فروشان
- آموزش تخصصی ابراز آلات شارژی

Clamp Multimeter



606+



606A+



606B+



606C+

FUNCTION	606+	606A+	606B+	606C+	Accuracy
DCV	200mV/2V/20V	600mV/6V/60V	600mV/6V/60V	600mV/6V/60V	$\pm(0.5\%+7)$
	200V	600V	600V	600V	$\pm(1.0\%+20)$
	600V	/	/	/	$\pm(1.2\%+20)$
ACV	2V/20V	6V/60V	6V/60V	6V/60V	$\pm(0.8\%+10)$
	200V	600V	600V	600V	$\pm(1.2\%+25)$
	600V	/	/	/	$\pm(1.5\%+25)$
LOW INPEDANCE ACV	2V/20V	6V/60V	6V/60V	6V/60V	$\pm(0.8\%+10)$
	200V	300V	300V	/	$\pm(1.2\%+25)$
	300V	/	/	/	$\pm(1.5\%+25)$
ACA	/	/	/	300V	$\pm(1.0\%+12)$
	2A	6A	6A	/	$\pm(4.0\%+50)$
	20A	60A	60A	/	$\pm(4.0\%+35)$
	200A/600A	600A	600A	/	$\pm(4.0\%+15)$
RESISTENCE	/	/	/	60A/600A	$\pm(4.0\%+10)$
	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω	600 Ω /6k Ω /60k Ω /600k Ω /6M Ω	600 Ω /6k Ω /60k Ω /600k Ω /6M Ω	600 Ω /6k Ω /60k Ω /600k Ω /6M Ω	$\pm(1.0\%+5)$
	20M Ω	20M Ω	20M Ω	20M Ω	$\pm(1.5\%+15)$
	/	60M Ω	60M Ω	60M Ω	$\pm(2.5\%+20)$
	/	6nF	6nF	6nF	$\pm(5.0\%+40)$
CAPACITANCE	/	60nF/600nF/6uF 60uF/600uF/6mF	60nF/600nF/6uF 60uF/600uF/6mF	60nF/600nF/6uF 60uF/600uF/6mF	$\pm(5.0\%+10)$
	/	10Hz/100Hz/1kHz/ 10kHz/100kHz/ 1MHz/10MHz	10Hz/100Hz/1kHz/ 10kHz/100kHz/ 1MHz/10MHz	10Hz/100Hz/1kHz/ /10kHz/100kHz/ 1MHz/10MHz	$\pm(0.3\%+3)$
	/	/	-20°C~1000°C (-4~1832)°F	-20°C~1000°C (-4~1832)°F	/

Display method	LCD display 5999 count	Max/Min	√
Maximum display	5999 count (606+ 1999count)	Low Z	√
Diode measurement	√	Working temperature and humidity	(0-40)°C <75%
Data retention	√	Storage temperature and humidity	(-10~50)°C<80%
NCV measurement	√	Automatic shut-down	About 15 minutes
Fire detection	√	Over-range display	the highest digit displays OL
Low voltage warning	√	Unit symbol	√
Flashlight lighting	√	Open jaws	35mm
True effective value	√	input resistance	10M Ω
INRUSH	606C+ only	Sampling rate	3 times/sec
VFC	606C+ only	power supply	Two AAA batteries

