



گروه فنی مهندسی جوش و برش مقدم

اعتماد از شما کیفیت و تخصص از ما



09153223758



051-37581400



<https://www.moghadamwelding>



<http://instagram.com/moghadam>



<https://t.me/moghadamwelding>



<https://whatsapp.com/channel>



<https://rubika.ir/moghadamwelding>



مشهد خیام شمالی 63 خیابان پردیس 3

برای کسب اطلاعات بیشتر بر روی لینک ها کلیک کنید

- 7 سال سابقه آموزش تعمیرات تخصصی دستگاه های جوش اینورتری تک فاز و 3 فاز
- 7 سال سابقه فروش قطعات الکترونیکی دستگاه جوش تک فاز و 3 فاز
- آموزش تخصصی تحلیل دستگاه های جوش اینورتری مختص ابراز فروشان
- آموزش تخصصی ابراز آلات شارژی

24A, 500V N-CHANNEL POWER MOSFET

DESCRIPTION


The UTC **24N50** is an N-channel mode power MOSFET using UTC's advanced technology to provide customers with planar stripe and DMOS technology. This technology allows a minimum on-state resistance and superior switching performance. It also can withstand high energy pulse in the avalanche and commutation mode.

The UTC **24N50** is generally applied in high efficiency switch mode power supplies, active power factor correction and electronic lamp ballasts based on half bridge topology.

FEATURES

- * $R_{DS(ON)} \leq 0.24 \Omega$ @ $V_{GS}=10V$, $I_D=12A$
- * High Switching Speed
- * 100% Avalanche Tested

SYMBOL




ORDERING INFORMATION


Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
24N50L-T47-T	24N50G-T47-T	TO-247	G	D	S	Tube
24N50L-T47S-T	24N50G-T47S-T	TO-247S	G	D	S	Tube
24N50L-T3P-T	24N50G-T3P-T	TO-3P	G	D	S	Tube

Note: Pin Assignment: G: Gate D: Drain S: Source

24N50G-T47-T (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube (2) T47: TO-247, T47S: TO-247S, T3P: TO-3P (3) G: Halogen Free and Lead Free, L: Lead Free
--	---



■ MARKING



■ **ABSOLUTE MAXIMUM RATINGS** ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V _{DSS}	500	V
Gate-Source Voltage		V _{GSS}	±30	V
Drain Current	Continuous (T _C =25°C)	I _D	24(Note 2)	A
	Pulsed (Note 3)	I _{DM}	96 (Note 2)	A
Avalanche Current (Note 3)		I _{AR}	24	A
Avalanche Energy	Single Pulsed (Note 4)	E _{AS}	1100	mJ
	Repetitive (Note 5)	E _{AR}	29	mJ
Peak Diode Recovery dv/dt (Note 5)		dv/dt	15	V/ns
Power Dissipation	TO-247/TO-247S	P _D	290	W
	TO-3P		300	W
Derate above 25°C				2.33
Junction Temperature		T _J	+150	°C
Storage Temperature		T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Drain current limited by maximum junction temperature.

3. Repetitive Rating: Pulse width limited by maximum junction temperature.

4. $L = 3.5\text{mH}$, $I_{AS} = 24\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^{\circ}\text{C}$

5. $I_{SD} \leq 24\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-247/TO-247S	θ_{JA}	50	$^{\circ}\text{C}/\text{W}$
	TO-3P		40	
Junction to Case	TO-247/TO-247S	θ_{JC}	0.43	$^{\circ}\text{C}/\text{W}$
	TO-3P		0.416	

ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$, unless otherwise specified)


PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =250μA, V _{GS} =0V	500			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =500V, V _{GS} =0V			50	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =+30V, V _{DS} =0V			+100	nA
	Reverse		V _{GS} =-30V, V _{DS} =0V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.0		4.0	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =10V, I _D =12A		0.15	0.24	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{GS} =0V, V _{DS} =25V, f=1.0MHz		3500	4500	pF
Output Capacitance		C _{OSS}			520	670	pF
Reverse Transfer Capacitance		C _{RSS}			55	70	pF
SWITCHING PARAMETERS							
Total Gate Charge		Q _G	V _{GS} =10V, V _{DS} =400V, I _D =24A (Note 1, 2)		90	120	nC
Gate to Source Charge		Q _{GS}			23		nC
Gate to Drain Charge		Q _{GD}			52		nC
Turn-ON Delay Time		t _{D(ON)}	V _{DD} =250V, I _D =24A, R _G =25Ω (Note 1, 2)		80	170	ns
Rise Time		t _R			250	500	ns
Turn-OFF Delay Time		t _{D(OFF)}			200	400	ns
Fall-Time		t _F			155	320	ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S				24	A
Maximum Body-Diode Pulsed Current		I _{SM}				96	A
Drain-Source Diode Forward Voltage		V _{SD}	I _S =24A, V _{GS} =0V			1.4	V
Body Diode Reverse Recovery Time		t _{rr}	I _S =24A, V _{GS} =0V,		250		ns
Body Diode Reverse Recovery Charge		Q _{rr}	dI _F /dt=100A/μs (Note 1)		1.1		μC

Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.


2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS


Gate Charge Test Circuit




Gate Charge Waveforms




Resistive Switching Test Circuit




Resistive Switching Waveforms







Unclamped Inductive Switching Test Circuit






Unclamped Inductive Switching Waveforms



■ TEST CIRCUITS AND WAVEFORMS

Peak Diode Recovery dv/dt Test Circuit & Waveforms

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.